



Lift master 5580 800N



Specifications:

| | |
|---------------------------------|---------------------------------|
| Operator: | Lift-Master 5580 |
| Motor pulling force: | 800N (80Kg approx) |
| Motor type: | AC (heavy duty) |
| Drive mechanism: | Full chain |
| Lifting capacity: | 80Kg's Automatic |
| Travel rate: | 133mm per second |
| Installed length: | N/A |
| Headroom clearance required: | 50mm |
| Maximum door opening: | 2.3m retractable |
| Soft-start / soft-stop feature: | No |
| Lighting: | |
| Wattage - | 1 x 40W (bulb not included) |
| Light delay time - | 4.5 minutes |
| Safety/emergency: | |
| Down cycle: safety reverse - | Yes |
| Up cycle: safety stop - | Yes |
| Automatic trolley reconnect - | Yes |
| Remote controls: | |
| Frequency - | 433Mhz |
| Number supplied in kit - | Three button keyfob. |
| Coding system - | Rolling code |
| Operating range - | 45m (open field) |
| Dimensions - | N/A |
| Battery - | 1 x 3 volt |
| Wall switch: | |
| Number supplied in kit - | One |
| Illuminated - | Yes |
| Dimensions - | 21mm x 21mm x 70mm |
| Warranty: | 2 years |
| Electrical: | |
| Voltage - | 230-240VAC, 50Hz |
| Wattage - | 400W |
| Current rating - | 2.5A |
| Standby power consumption - | 2.6W |
| Length of power cord - | 1.2m |
| Operating temperature: | -35°C to 65°C |
| Shipping Weight: | |
| Motor & assemblies | 12.2kg |
| Rail | 7.5kg |
| Construction: | Steel (rail, chassis & trolley) |