

### Mechanical Specifications

<b>MOTOR</b>	Heavy-Duty 24V DC Motor with thermal protection and permanently lubricated gear.
<b>DRIVE MECHANISM</b>	Drive Means: Internal Chain and Sprocket Reduction Means: Gear Ratio 63:1
<b>ADJUSTMENTS</b>	Force: Electronic/Internal Auto Force Limit; Internal/Electronic
<b>TRAVEL RATE</b>	Approximately 7.6" per second
<b>SHIPPING WEIGHT</b>	Entire System: 31 lbs.
<b>MATERIALS</b>	Chassis: Steel Plastic cover

### Electrical Specifications


<b>POWER</b>	Powerhead Voltage: 120V AC, 60Hz; Wattage:120; Current Rating: 1.0A; UL Listed: Yes; Length of Cord: 6 feet (3 prong); Worklight Voltage: 120V AC, 60Hz; Wattage: 200; Current Rating: 1.7A; UL Listed: Yes; Length of Cord: 6 feet (2 prong)
<b>LOGIC TYPE</b>	Solid-State Microcontroller with Built-in Surge Suppressor
<b>LIGHTING</b>	Number of Bulbs: 2; Maximum Wattage: 100 x 2 Length of Light Delay: Adjustable Type of Light Delay: Solid-State UL Listed: Yes

CHAMBERLAIN®  
**LiftMaster**



### RESIDENTIAL JACKSHAFT OPENER – 3800







**Optional EverCharge™  
Battery Backup System**



**Remote Light Included**



**Cable Tension  
Monitor Included**



**Power Lock Included**