

## XENYX X1832USB

Premium 18-Input 3/2-Bus Mixer with XENYX Mic Preamps & Compressors, British EQs, 24-Bit Multi-FX Processor, USB/Audio Interface and energyXT2.5 Compact BEHRINGER Edition Music Production Software

- \* Premium ultra-low noise, high headroom analog mixer
- \* 6 state-of-the-art, phantom-powered XENYX Mic Preamps comparable to stand-alone boutique preamps
- \* 6 studio-grade compressors with super-easy "one-knob" functionality and control LED for professional vocal and instrumental sound
- \* Neo-classic "British" 3-band EQs with semi-parametric mid band for warm and musical sound
- \* New studio-grade FX processor with 16 editable presets including reverb, chorus, flanger, delay, pitch shifter, multi-effects, Tap function and storable user parameter settings
- \* Built-in stereo USB/Audio Interface to connect directly to your computer. Free audio recording, editing and podcasting software plus 150 instrument/effect plug-ins and ultra-low latency driver included
- \* Revolutionary energyXT2.5 Compact BEHRINGER Edition music production software included with feature-rich audio/MIDI sequencer that loads almost instantaneously on all computer platforms
- \* 9-band stereo graphic EQ allows precise frequency correction of monitor or main mixes
- \* Revolutionary FBQ Feedback Detection System instantly reveals critical frequencies
- \* Breathtaking XPQ 3D stereo surround effect for more vitality and enhanced stereo image
- \* Voice Canceller function for easy-to-use sing-along applications
- \* Channel inserts on each mono channel for flexible connection of outboard equipment
- \* 3 aux sends per channel: 1 pre fader for monitoring, 1 pre/post fader switchable for monitoring/FX applications, 1 post fader (for internal FX or as external send)
- \* Clip LEDs, mute, main mix and subgroup routing switches, solo and PFL functions on all channels
- \* 2 subgroups with separate outputs for added routing flexibility and 2 multi-functional stereo aux returns with flexible routing
- \* Balanced main mix outputs with " jack and gold-plated XLR connectors, separate control room, headphones and stereo rec outputs
- \* Control room/phones outputs with multi-input source matrix; rec inputs assignable to main mix or control room/phones outputs
- \* "Planet Earth" switching power supply for maximum flexibility (100 - 240 V~), noise-free audio, superior transient response plus low power consumption for energy saving
- \* High-quality components and exceptionally rugged construction ensure long life
- \* Conceived and designed by BEHRINGER Germany



www.fes.in.th

